



ROYAL OAK FLOORS

ARCHITECT COLLECTION

TECHNICAL DATA SHEET

SPECIFICATION DETAILS

Product	Engineered Timber Flooring	Profile	Tongue & Groove End-Matched
Timber Species	European Oak	Finish	UV-Cured Lacquer UV Oil (French Grey ONLY)
Plank Sizes	90mm x 1900mm x 15mm 190mm x 1900mm x 15mm 260mm x 2200mm x 15mm 190mm x 1900mm x 20mm 260mm x 2200mm x 20mm	Shorts	Plank : Maximum 30% Herringbone : Nil Chevron : Nil
Herringbone Sizes	148mm x 888mm x 15mm 90mm x 450mm x 15mm	Waste Allowance	Plank : Minimum 10% Herringbone : 15% - 20% Chevron : 15% - 20%
Chevron Size	90mm x 520mm x 15mm	Installation	Direct Stick Glue & Secret Nail Floating (Plank ONLY)
Nosing Sizes	1300mm & 1800mm	Warranty	Seven (7) Year Structural Warranty
Oak Layer	4mm (15mm thick board) 6mm (20mm thick board)		
Grade	Mixed		















TEST RESULTS & CERTIFICATES

Wet Pendulum Test	AS 4586-2013 Appendix A Classification: P2
Dry Floor Friction Test	AS 4586-2013 Appendix B Classification: D1
Fire Test - Flooring	AS/ISO 9239.1-2003
* UV-Cured Lacquer ONLY	15mm : CHF Value - 3.8 kW/m2 Smoke Value - 19% 20mm : CHF Value - 4.0 kW/m2 Smoke Value - 54%
BCA Group Number	AS 5637.1-2015 Classification: 3
Emission Test	VOC : 0.037 mg/m2/hr Formaldehyde : 0.012 mg/m2/hr

SUSTAINABLY SOURCED

All timber components are sourced from PEFC or FSC plantations, meaning raw material harvesting is closely managed to promote sustainable forestry practices.

COLOUR RANGE

		
Danish White	Light Oak	White Smoked
		
Natural Suede	Tanned Oak	Toasted Oak
		
Smoked & Limed	Smoked	Smoked & Black
		
Saddle Oak	French Grey	Mink Grey
		
Dark Oak	Brown Black	