






# ARCHITECT

TECHNICAL DATA SHEET

SPECIFICATION DETAILS

Product	Engineered Timber Flooring
Timber species	European Oak
Grade	Mixed
Profile	Tongue & Groove   End-Matched
Finish	UV-Cured Lacquer UV Oil (French Grey Only)
Shorts	Boards: Maximum 30% Herringbone: Nil Chevron: Nil
Waste allowance	Boards: Minimum 10% Herringbone: 15% - 20% Chevron: 15% - 20%
Installation	Direct Stick Glue and Secret Nail Floating (Boards Only)
Warranty	Seven (7) Year Structural Warranty



Board	90mm x 1900mm x 15mm 190mm x 1900mm x 15mm 260mm x 2200mm x 15mm 190mm x 1900mm x 20mm 260mm x 2200mm x 20mm
Herringbone	90mm x 450mm x 15mm 148mm x 888mm x 15mm
Chevron	90mm x 520mm x 15mm
Stair nosing	1300mm x 1800mm
Oak layer	4mm (15mm thick board) 6mm (20mm thick board)

CERTIFICATIONS

Wet Pendulum Test	AS 4586-2013 Appendix A Classification: P2
Dry Floor Friction Test	AS 4586-2013 Appendix B Classification: D1
Fire Test - Flooring	AS/ISO 9239.1-2003
UV-Cured Lacquer Only	15mm: CHF value - 3.8kW/m² 15mm: Smoke value - 19% 20mm: CHF value - 4.0 kW/m² 20mm: Smoke value - 54%
BCA Group Number	AS 5637.1-2015 Classification: 3
Emission Test	VOC: 0.037 mg/m2/hr Formaldehyde: 0.012 mg/m2/hr

SUSTAINABLY SOURCED



All timber components are sourced from FSC®-certified forests, managed in line with rigorous standards that support sustainable forestry, protect biodiversity, and respect the rights of Indigenous Peoples, workers, and local communities.

COLOUR RANGE

		
Danish White	Light Oak	White Smoked
		
Natural Suede	Tanned Oak	Toasted Oak
		
Smoked & Limed	Smoked & Black	Saddle Oak
		
French Grey	Mink Grey	Dark Oak