




ARCHITECT

TECHNICAL DATA SHEET

SPECIFICATION DETAILS

| | |
|-----------------|---|
| Product | Engineered Timber Flooring |
| Timber species | European Oak |
| Grade | Mixed |
| Profile | Tongue & Groove End-Matched |
| Finish | UV-Cured Lacquer |
| Shorts | Boards: Maximum 30% Herringbone: Nil Chevron: Nil |
| Waste allowance | Boards: Minimum 10% Herringbone: 15% - 20% Chevron: 15% - 20% |
| Installation | Direct Stick Glue and Secret Nail Floating (Boards Only) |
| Warranty | Seven (7) Year Structural Warranty |




Board

90mm x 1900mm x 15mm
190mm x 1900mm x 15mm
260mm x 2200mm x 15mm
190mm x 1900mm x 20mm
260mm x 2200mm x 20mm



Herringbone

90mm x 450mm x 15mm
148mm x 888mm x 15mm



Chevron

90mm x 520mm x 15mm

Stair nosing

1300mm
1800mm

Oak layer

4mm (15mm thick board)
6mm (20mm thick board)

CERTIFICATIONS


| | |
|-------------------------|---|
| Wet Pendulum Test | AS 4586-2013 Appendix A Classification: P2 |
| Dry Floor Friction Test | AS 4586-2013 Appendix B Classification: D1 |
| Fire Test - Flooring | AS/ISO 9239.1-2003 |
| UV-Cured Lacquer Only | 15mm: CHF value - 3.8kW/m ² 15mm: Smoke value - 19% 20mm: CHF value - 4.0 kW/m ² 20mm: Smoke value - 54% |
| BCA Group Number | AS 5637.1-2015 Classification: 3 |
| Emission Test | VOC: 0.037 mg/m ² /hr Formaldehyde: 0.012 mg/m ² /hr |

SUSTAINABLY SOURCED




All timber components are sourced from FSC®-certified forests, managed in line with rigorous standards that support sustainable forestry, protect biodiversity, and respect the rights of Indigenous Peoples, workers, and local communities.


COLOUR RANGE




Dune



White Smoked



Light Oak



Natural Suede



Tanned Oak




Toasted Oak




Smoked & Black




Saddle Oak



Marle



Cashmere



Sable



Dark Oak