




ARTISAN

TECHNICAL DATA SHEET

SPECIFICATION DETAILS

Product	Engineered Timber Flooring
Timber species	European Oak
Grade	Feature
Profile	Tongue & Groove End-Matched
Finish	UV-Oil
Shorts	Boards: Maximum 30% Herringbone: Nil
Waste allowance	Boards: Minimum 10% Herringbone: 15% - 20%
Installation	Direct Stick Glue and Secret Nail Floating (Boards Only)
Warranty	Seven (7) Year Structural Warranty



Board

190mm x 1900mm x 15mm
260mm x 2200mm x 15mm
190mm x 1900mm x 20mm
260mm x 2200mm x 20mm



Herringbone

148mm x 888mm x 15mm

Stair nosing

1300mm
1800mm

Oak layer

4mm (15mm thick board)
6mm (20mm thick board)

CERTIFICATIONS

Wet Pendulum Test	AS 4586-2013 Appendix A Classification: P2
Dry Floor Friction Test	AS 4586-2013 Appendix B Classification: D1
Fire Test - Flooring	AS/ISO 9239.1-2003 15mm: CHF value - 3.6kW/m ² 15mm: Smoke value - 36% 20mm: CHF value - 3.8 kW/m ² 20mm: Smoke value - 29%
BCA Group Number	AS 5637.1-2015 Classification: 3
Emission Test	VOC: 0.037 mg/m ² /hr Formaldehyde: 0.012 mg/m ² /hr

COLOUR RANGE



Aged Smoked



Aged Smoked & Limed



Wheat Fields


SUSTAINABLY SOURCED



All timber components are sourced from FSC®-certified forests, managed in line with rigorous standards that support sustainable forestry, protect biodiversity, and respect the rights of Indigenous Peoples, workers, and local communities.

SPECIFICATION DETAILS

Product	Engineered Timber Flooring
Timber species	European Oak
Grade	Rustic
Profile	Tongue & Groove End-Matched
Finish	Hardwax Oil
Shorts	Boards: Maximum 30%
Waste allowance	Boards: Minimum 10%
Installation	Direct Stick Glue and Secret Nail Floating (Boards Only)
Warranty	Seven (7) Year Structural Warranty



Board
189mm x 1830mm x 18mm

Stair nosing 1300mm
1800mm

Oak layer 4mm

CERTIFICATIONS

Wet Pendulum Test	AS 4586-2013 Appendix A Classification: Z (P1)
Dry Floor Friction Test	AS 4586-2013 Appendix B Classification: F
Fire Test - Flooring	AS/ISO 9239.1-2003 18mm: CHF value - 5.2kW/m ² 15mm: Smoke value - 7%
BCA Group Number	AS 5637.1-2015 Classification: 3
Emission Test	VOC: 0.037 mg/m ² /hr Formaldehyde: 0.012 mg/m ² /hr

COLOUR RANGE



Antique Stout Brown



Antique Ale Brown


SUSTAINABLY SOURCED



All timber components are sourced from FSC®-certified forests, managed in line with rigorous standards that support sustainable forestry, protect biodiversity, and respect the rights of Indigenous Peoples, workers, and local communities.

SPECIFICATION DETAILS

Product	Engineered Timber Flooring
Timber species	European Oak
Grade	Feature
Profile	Tongue & Groove End-Matched
Finish	UV-Cured Lacquer
Shorts	Boards: Maximum 30% Herringbone: Nil
Waste allowance	Boards: Minimum 10% Herringbone: 15% - 20%
Installation	Direct Stick Glue and Secret Nail Floating (Boards Only)
Warranty	Seven (7) Year Structural Warranty



Board

189mm x 1830mm x 15mm
260mm x 2200mm x 15mm
189mm x 1830mm x 20mm
260mm x 2200mm x 20mm



Herringbone

148mm x 888mm x 15mm

Stair nosing

1300mm
1800mm

Oak layer

4mm (15mm thick board)
6mm (20mm thick board)

CERTIFICATIONS

Wet Pendulum Test	AS 4586-2013 Appendix A Classification: 4
Dry Floor Friction Test	AS 4586-2013 Appendix B Classification: D1
Fire Test - Flooring	AS/ISO 9239.1-2003 20mm: CHF value - 3.2 kW/m ² 20mm: Smoke value - 116%
BCA Group Number	AS 5637.1-2015 Classification: 3
Emission Test	VOC: 0.037 mg/m ² /hr Formaldehyde: 0.012 mg/m ² /hr

COLOUR RANGE



Arctic Grey



Ash Grey



Peppercorn Grey

SUSTAINABLY SOURCED



All timber components are sourced from FSC®-certified forests, managed in line with rigorous standards that support sustainable forestry, protect biodiversity, and respect the rights of Indigenous Peoples, workers, and local communities.