



ROYAL OAK FLOORS
by Harper & Sandlands


BROWN BLACK

ARCHITECT COLLECTION



TIMBER SPECIES	European Oak veneer with Poplar core
STRIP SIZE	158mm W x 1830mm L x 10mm D – 3mm veneer 189mm W x 1830mm L x 15mm D – 4mm veneer 260mm W x 2200mm L x 15mm D – 4mm veneer 189mm W x 1830mm L x 20mm D – 6mm veneer 260mm W x 2200mm L x 20mm D – 6mm veneer
HERRINGBONE SIZE	148mm W x 888mm L x 15mm D – 4mm veneer
CHEVRON SIZE	305mm W x 1672mm L x 15mm D – 4mm veneer
GRADING	Mixed grade
PROFILE	Tongue & Groove
FINISH	Aluminium Oxide 9% gloss
INSTALLATION METHOD	Direct stick, glue & secret nail (floating – see spec)


SPECIFICATION DATA	
SLIP TEST	Class: P2 (AS 4586-2013 Appendix A)
WET PENDULUM	Class: D1 (AS 4586-2013 Appendix B)
FIRE TEST	Mean 3.5 kW/m ² – 10mm Mean 3.8 kW/m ² – 15mm Mean 4.0 kW/m ² – 20mm
CHF VALUE (AS/ISO 9239.1-2003)	Mean 36%. Min. – 10mm Mean 19%. Min. – 15mm Mean 54%. Min. – 20mm
SMOKE VALUE (AS/ISO 9239.1-2003)	Group 3
BCA GROUP NUMBER (AS 5637.1-2015)	
VOC EMISSION RATE	0.037 mg/m ² /hr
FORMALDEHYDE EMISSION RATE	0.012 mg/m ² /hr



20mm – multiply construction.
6mm Oak Layer with 14mm base.



15mm – 3 layer construction.
4mm Oak Layer with 11mm base.



10mm – multiply construction.
3mm Oak Layer with 7mm base.

DISCLAIMER

As timber is a natural product, variations can occur between samples, in showroom product displays and printed and online imagery. Please ensure you review your sales order and the actual product PRIOR to your flooring being installed as although we endeavour to represent our product to the best of our ability this natural variation can cause differences.