

ARTISAN COLLECTION - INTRINSIC BLACK

TECHNICAL DATA SHEET


SPECIFICATION DETAILS

| | | | |
|-------------------------|-------------------------------|------------------------|------------------------------------|
| Product | Engineered Timber Flooring | Shorts | Plank : Maximum 30% |
| Timber Species | European Oak | | Herringbone : Nil |
| Plank Size | 190mm x 1900mm x 15mm | | Chevron : Nil |
| Herringbone Size | 90mm x 450mm x 15mm | Waste Allowance | Plank : Minimum 10% |
| Chevron Size | 90mm x 540mm x 15mm | | Herringbone : 15% - 20% |
| Oak Layer | 3mm (15mm thick board) | | Chevron : 15% - 20% |
| Nosing Sizes | 1300mm & 1800mm | Installation | Direct Stick |
| Grade | Mixed | | Glue & Secret Nail |
| Profile | Tongue & Groove End-Matched | | Floating (Plank ONLY) |
| Texture | Smooth | Warranty | Seven (7) Year Structural Warranty |
| Finish | UV-Cured Lacquer | | |

TEST RESULTS & CERTIFICATES

| | |
|--------------------------------|--|
| Wet Pendulum Test | AS 4586-2013 Appendix A Classification: P2 |
| Dry Floor Friction Test | AS 4586-2013 Appendix B Classification: D1 |
| Fire Test - Flooring | AS/ISO 9239.1-2003 15mm : CHF Value - 3.8 kW/m2 Smoke Value - 19% 20mm : CHF Value - 4.0 kW/m2 Smoke Value - 54% |
| BCA Group Number | AS 5637.1-2015 Classification: 3 |
| Emission Test | VOC : 0.037 mg/m2/hr Formaldehyde : 0.012 mg/m2/hr |

COLOUR RANGE



Intrinsic Black

SUSTAINABLY SOURCED

All timber components are sourced from PEFC or FSC plantations, meaning raw material harvesting is closely managed to promote sustainable forestry practices.