



# ARTISAN COLLECTION - INTRINSIC BLACK

## TECHNICAL DATA SHEET

### SPECIFICATION DETAILS

---

<b>Product</b>	Engineered Timber Flooring	<b>Shorts</b>	Plank : Maximum 30%
<b>Timber Species</b>	European Oak		Herringbone : Nil
<b>Plank Size</b>	180mm x 1860mm x 15mm		Chevron : Nil
<b>Herringbone Size</b>	90mm x 450mm x 15mm	<b>Waste Allowance</b>	Plank : Minimum 10%
<b>Chevron Size</b>	90mm x 540mm x 15mm		Herringbone : 15% - 20%
<b>Oak Layer</b>	Plank - 4mm Herringbone & Chevron - 3mm (15mm thick board)	<b>Installation</b>	Chevron : 15% - 20%
<b>Nosing Sizes</b>	1300mm & 1800mm		Direct Stick
<b>Grade</b>	Mixed		Glue & Secret Nail
<b>Profile</b>	Tongue & Groove   End-Matched	<b>Warranty</b>	Floating (Plank ONLY)
<b>Texture</b>	Smooth		Seven (7) Year Structural Warranty
<b>Finish</b>	UV-Cured Lacquer		


### TEST RESULTS & CERTIFICATES

---

<b>Wet Pendulum Test</b>	AS 4586-2013 Appendix A Classification: P2
<b>Dry Floor Friction Test</b>	AS 4586-2013 Appendix B Classification: D1
<b>Fire Test - Flooring</b>	AS/ISO 9239.1-2003 15mm : CHF Value - 3.8 kW/m <sup>2</sup> Smoke Value - 19% 20mm : CHF Value - 4.0 kW/m <sup>2</sup> Smoke Value - 54%
<b>BCA Group Number</b>	AS 5637.1-2015 Classification: 3
<b>Emission Test</b>	VOC : 0.037 mg/m <sup>2</sup> /hr Formaldehyde : 0.012 mg/m <sup>2</sup> /hr

### COLOUR RANGE

---



Intrinsic Black

### SUSTAINABLY SOURCED

---

All timber components are sourced from PEFC or FSC plantations, meaning raw material harvesting is closely managed to promote sustainable forestry practices.