



# ARCHITECT COLLECTION

## TECHNICAL DATA SHEET

### SPECIFICATION DETAILS

<b>Product</b>	Engineered Timber Flooring	<b>Profile</b>	Tongue & Groove   End-Matched
<b>Timber Species</b>	European Oak	<b>Finish</b>	UV-Cured Lacquer
<b>Plank Sizes</b>	190mm x 1900mm x 15mm 260mm x 2200mm x 15mm 190mm x 1900mm x 20mm 260mm x 2200mm x 20mm	<b>Shorts</b>	UV Oil (French Grey ONLY)  Plank : Maximum 30% Herringbone : Nil Chevron : Nil
<b>Herringbone Sizes</b>	148mm x 888mm x 15mm 90mm x 450mm x 15mm	<b>Waste Allowance</b>	Plank : Minimum 10% Herringbone : 15% - 20% Chevron : 15% - 20%
<b>Chevron Size</b>	90mm x 520mm x 15mm	<b>Installation</b>	Direct Stick Glue & Secret Nail Floating (Plank ONLY)
<b>Nosing Sizes</b>	1300mm & 1800mm	<b>Warranty</b>	Seven (7) Year Structural Warranty
<b>Oak Layer</b>	4mm (15mm thick board) 6mm (20mm thick board)		
<b>Grade</b>	Mixed		















### TEST RESULTS & CERTIFICATES

<b>Wet Pendulum Test</b>	AS 4586-2013 Appendix A Classification: P2
<b>Dry Floor Friction Test</b>	AS 4586-2013 Appendix B Classification: D1
<b>Fire Test - Flooring</b>	AS/ISO 9239.1-2003
<b>* UV-Cured Lacquer ONLY</b>	15mm : CHF Value - 3.8 kW/m2 Smoke Value - 19% 20mm : CHF Value - 4.0 kW/m2 Smoke Value - 54%
<b>BCA Group Number</b>	AS 5637.1-2015 Classification: 3
<b>Emission Test</b>	VOC : 0.037 mg/m2/hr Formaldehyde : 0.012 mg/m2/hr

### SUSTAINABLY SOURCED

All timber components are sourced from PEFC or FSC plantations, meaning raw material harvesting is closely managed to promote sustainable forestry practices.

### COLOUR RANGE

		
Danish White	Light Oak	White Smoked
		
Natural Suede	Tanned Oak	Toasted Oak
		
Smoked & Lined	Smoked	Smoked & Black
		
Saddle Oak	French Grey	Mink Grey
		
Dark Oak	Brown Black	